

**压敏电阻MOV Metal Oxide Varistor**

Part No	Max Continuous Voltage		Varistor Voltage	Max Clamping Voltage		Withstanding Surge Current (8/20us)				Rated Power	Energy 10/1000us		Capacitance @1KHz
	VAC (rms)	VDC	V1mA	Vp	1p	General(A)		High Surge(A)		P	General	KJ	Cp
	V	V	V	V	A	1Time	2Time	1Time	2Time	W	J	J	PF
10D180L	10	14	18(15-21)	38	5	500	250	1000	500	0.05	2.8	3	5600
10D220K	14	18	22(20-24)	43	5	500	250	1000	500	0.05	4.5	5	4500
10D270K	17	22	27(24-30)	53	5	500	250	1000	500	0.05	6	6.5	3700
10D330K	20	26	33(30-36)	65	5	500	250	1000	500	0.05	7.4	8	3000
10D390K	25	31	39(35-43)	77	5	500	250	1000	500	0.05	9.1	9.5	2600
10D470K	30	38	47(42-52)	93	5	500	250	1000	500	0.05	10.8	11	2100
10D560K	35	45	56(50-62)	110	5	500	250	1000	500	0.05	12.9	13	1800
10D680K	40	56	68(61-75)	135	5	500	250	1000	500	0.05	15.4	16	1500
10D820K	50	65	82(74-90)	135	25	2500	1250	3500	2500	0.4	16.8	17	1200
10D101K	60	85	100(90-110)	165	25	2500	1250	3500	2500	0.4	18.2	18.5	1000
10D121K	75	100	120(108-132)	200	25	2500	1250	3500	2500	0.4	21	21.5	830
10D151K	95	125	150(135-165)	250	25	2500	1250	3500	2500	0.4	25.2	26	670
10D181K	115	150	180(162-198)	300	25	2500	1250	3500	2500	0.4	30.8	38	560
10D201K	130	170	200(185-225)	340	25	2500	1250	3500	2500	0.4	42	42.5	500
10D221K	140	180	220(198-242)	360	25	2500	1250	3500	2500	0.4	46.2	46.5	450
10D241K	150	200	240(216-264)	395	25	2500	1250	3500	2500	0.4	50.4	51	420
10D271K	175	225	270(243-297)	455	25	2500	1250	3500	2500	0.4	57.4	58	370
10D301K	190	250	300(270-330)	500	25	2500	1250	3500	2500	0.4	63	63.5	330
10D331K	210	275	330(297-363)	550	25	2500	1250	3500	2500	0.4	68.6	69	300
10D361K	230	300	360(324-396)	595	25	2500	1250	3500	2500	0.4	74.2	75	280
10D391K	250	320	390(351-429)	650	25	2500	1250	3500	2500	0.4	81.2	82	260
10D431K	275	350	430(387-473)	710	25	2500	1250	3500	2500	0.4	88.2	89	230
10D471K	300	385	470(423-517)	775	25	2500	1250	3500	2500	0.4	96	100	210
10D511K	320	415	510(459-561)	845	25	2500	1250	3500	2500	0.4	98	102	200
10D561K	350	460	560(504-616)	925	25	2500	1250	3500	2500	0.4	100	104	180
10D621K	385	505	620(558-682)	1025	25	2500	1250	3500	2500	0.4	102	106	160
10D681K	420	560	680(612-748)	1120	25	2500	1250	3500	2500	0.4	104	108	150
10D751K	460	615	750(675-825)	1240	25	2500	1250	3500	2500	0.4	110	118	140
10D781K	485	640	780(702-858)	1290	25	2500	1250	3500	2500	0.4	118	120	130
10D821K	510	670	820(738-902)	1355	25	2500	1250	3500	2500	0.4	122	125	120
10D911K	550	745	910(819-1001)	1500	25	2500	1250	3500	2500	0.4	128	134	110
10D951K	575	765	950(855-1045)	1570	25	2500	1250	3500	2500	0.4	130	134	100
10D102K	625	825	1000(900-1100)	1650	25	2500	1250	3500	2500	0.4	133	140	90
10D112K	680	895	1100(990-1210)	1815	25	2500	1250	3500	2500	0.4	150	155	80
10D122K	750	980	1200(1080-1320)	2000	25	2500	2500	3500	2500	0.4	155	160	70
10D152K	900	1200	1500(1350-1650)	2475	25	2500	1250	3500	2500	0.4	160	165	60
10D182K	1000	1465	1800(1620-1980)	2970	25	2500	1250	3500	2500	0.4	180	185	50