

**压敏电阻MOV Metal Oxide Varistor**

Part No	Max Continuous Voltage		Varistor Voltage	Max Clamping Voltage		Withstanding Surge Current (8/20us)				Rated Power	Energy 10/1000us		Capacitance @1KHz
	VAC (rms)	VDC		Vp	1p	General(A)		High Surge(A)			P	General	
	V	V	V	V	A	1Time	2Time	1Time	2Time	W	J	J	PF
14D180L	10	14	18(15-21)	38	10	1000	500	2000	1000	0.1	6.6	7	11100
14D220K	14	18	22(20-24)	43	10	1000	500	2000	1000	0.1	7.6	8	9100
14D270K	17	22	27(24-30)	53	10	1000	500	2000	1000	0.1	9.7	10	7400
14D330K	20	26	33(30-36)	65	10	1000	500	2000	1000	0.1	12.3	12.5	6100
14D390K	25	31	39(35-43)	77	10	1000	500	2000	1000	0.1	13.2	13.5	5100
14D470K	30	38	47(42-52)	93	10	1000	500	2000	1000	0.1	16.8	17	4300
14D560K	35	45	56(50-62)	110	10	1000	500	2000	1000	0.1	19.6	20	3600
14D680K	40	56	68(61-75)	135	10	1000	500	2000	1000	0.1	23.8	24	2900
14D820K	50	65	82(74-90)	135	50	4500	2500	6000	5000	0.6	29.4	30	2400
14D101K	60	85	100(90-110)	165	50	4500	2500	6000	5000	0.6	33.6	35	2000
14D121K	75	100	120(108-132)	200	50	4500	2500	6000	5000	0.6	40.6	42	1700
14D151K	95	125	150(135-165)	250	50	4500	2500	6000	5000	0.6	51.8	53	1300
14D181K	115	150	180(162-198)	300	50	4500	2500	6000	5000	0.6	58.8	74	1100
14D201K	130	170	200(185-225)	340	50	4500	2500	6000	5000	0.6	75.2	78.6	1000
14D221K	140	180	220(198-242)	360	50	4500	2500	6000	5000	0.6	79.8	80.5	900
14D241K	150	200	240(216-264)	395	50	4500	2500	6000	5000	0.6	82.6	86	830
14D271K	175	225	270(243-297)	455	50	4500	2500	6000	5000	0.6	84	94	740
14D301K	190	250	300(270-330)	500	50	4500	2500	6000	5000	0.6	103	105	670
14D331K	210	275	330(297-363)	550	50	4500	2500	6000	5000	0.6	112	115	610
14D361K	230	300	360(324-396)	595	50	4500	2500	6000	5000	0.6	123	130	560
14D391K	250	320	390(351-429)	650	50	4500	2500	6000	5000	0.6	135	140	510
14D431K	275	350	430(387-473)	710	50	4500	2500	6000	5000	0.6	145	155	460
14D471K	300	385	470(423-517)	775	50	4500	2500	6000	5000	0.6	147	175	430
14D511K	320	415	510(459-561)	845	50	4500	2500	6000	5000	0.6	148	180	390
14D561K	350	460	560(504-616)	925	50	4500	2500	6000	5000	0.6	150	186	360
14D621K	385	505	620(558-682)	1025	50	4500	2500	6000	5000	0.6	155	188	320
14D681K	420	560	680(612-748)	1120	50	4500	2500	6000	5000	0.6	160	190	290
14D751K	460	615	750(675-825)	1240	50	4500	2500	6000	5000	0.6	180	190	270
14D781K	485	640	780(702-858)	1290	50	4500	2500	6000	5000	0.6	190	210	260
14D821K	510	670	820(738-902)	1355	50	4500	2500	6000	5000	0.6	203	211	230
14D911K	550	745	910(819-1001)	1500	50	4500	2500	6000	5000	0.6	208	235	220
14D951K	575	765	950(855-1045)	1570	50	4500	2500	6000	5000	0.6	212	255	200
14D102K	625	825	1000(900-1100)	1650	50	4500	2500	6000	5000	0.6	217	310	180
14D112K	680	895	1100(990-1210)	1815	50	4500	2500	6000	5000	0.6	266	330	130
14D122K	750	980	1200(1080-1320)	2000	50	4500	2500	6000	5000	0.6	336	420	130
14D152K	900	1200	1500(1350-1650)	2475	50	4500	2500	6000	5000	0.6	336	420	110
14D182K	1000	1465	1800(1620-1980)	2970	50	4500	2500	6000	5000	0.6	340	510	110