

压敏电阻MOV Metal Oxide Varistor

Part No	Max Continuous Voltage		Varistor Voltage	Max Clamping Voltage		Withstanding Surge Current (8/20us)		Rated Power	Energy 10/1000us
	VAC (rms)	VDC	V1mA	Vp	1p	I _{max}	I _n	P	General
	V	V	V	V	A	A	A	W	J
34S201K	130	170	200(185-225)	340	150	40000	20000	1.2	340
34S221K	140	180	220(198-242)	360	150	40000	20000	1.2	360
34S241K	150	200	240(216-264)	395	150	40000	20000	1.2	435
34S271K	175	225	270(243-297)	455	150	40000	20000	1.2	465
34S301K	190	250	300(270-330)	500	150	40000	20000	1.2	490
34S331K	210	275	330(297-363)	550	150	40000	20000	1.2	520
34S361K	230	300	360(324-396)	595	150	40000	20000	1.2	580
34S391K	250	320	390(351-429)	650	150	40000	20000	1.2	645
34S431K	275	350	430(387-473)	710	150	40000	20000	1.2	720
34S471K	300	385	470(423-517)	775	150	40000	20000	1.2	785
34S511K	320	415	510(459-561)	845	150	40000	20000	1.2	840
34S561K	350	460	560(504-616)	925	150	40000	20000	1.2	915
34S621K	385	505	620(558-682)	1025	150	40000	20000	1.2	985
34S681K	420	560	680(612-748)	1120	150	40000	20000	1.2	1120
34S751K	460	615	750(675-825)	1240	150	40000	20000	1.2	1160
34S781K	485	640	780(702-858)	1290	150	40000	20000	1.2	1210
34S821K	510	670	820(738-902)	1355	150	40000	20000	1.2	1280
34S911K	550	745	910(819-1001)	1500	150	40000	20000	1.2	1355
34S951K	575	765	950(855-1045)	1570	150	40000	20000	1.2	1455
34S102K	625	825	1000(900-1100)	1650	150	40000	20000	1.2	1560
34S112K	680	895	1100(990-1210)	1815	150	40000	20000	1.2	1610
34S122K	750	980	1200(1080-1320)	2000	150	40000	20000	1.2	1690
34S152K	900	1200	1500(1350-1650)	2475	150	40000	20000	1.2	1720
34S182K	1000	1465	1800(1620-1980)	2970	150	40000	20000	1.2	1760